

LIGHTING REGULATION - RACK 19" DIMMERS

POWER 6-3 TR (TERMINALS) // POWER 6-3 TR (HARTING)

Dimmers of 6 channels and 3KW per channel

6-channel dimmer of 3 kW per channel. Manufactured in 2 units of rack 19".

Load is duly controlled by 40Amp. triacs which are cooled by a black anodised aluminium radiator and a fan.

Output to the loads are by guide terminals (TERMINALS model) or Harting multiconnector (HARTING model).

LCD frontal display for showing the information given by the power unit and for programming the different available options.

The output charge channels are protected separately by a 16-Amp breaker per each channel.

Test function for external checking of the signal and power installation.

Made according to CE specifications.

These are the programmable functions available in this unit:

- Channel number addressing
- Selecting the curve type for each channel
- Minimum and maximum levels per channel
- Selecting the chaser to run
- Test function



References: 07000043
07000045

<i>Weight</i>	10 Kg.
<i>Dimensions</i>	482x88x390 mm
<i>Exterior finish</i>	Black
<i>Power supply</i>	Three-phase: 400V 50Hz

Other characteristics:

- Minimum load per channel 100W
- Maximum load per channel 3.000W
- Total maximum load 18.000W
- Output breakdown switch 16 Amp per channel
- Digital Input Signal DMX-512 (1990)
- Digital input connector XLR-5 pins